

Product data sheet

Specifications



Rack ATS, 230V, 16A, (2) IEC 309 in, (1) IEC 309 out



AP4422

Overview

Lead time Usually in Stock

Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Input Connection Type	IEC 60309 16 A 2P+E
Number of rack unit	1U
Cable length	8 ft (2.44 m)
Number of cables	2
Provided Equipment	Mounting Hardware Rack Mounting brackets Serial configuration cable

Physical

Color	Black
Height	1.73 in (4.4 cm)
Width	17.01 in (43.2 cm)
Depth	9.29 in (23.6 cm)
Net Weight	9.28 lb(US) (4.21 kg)
Mounting Location	Front Rear
Mounting preference	No preference
Mounting Mode	Rack-mounted

Input

Input Frequency	50/60 Hz
Max line current	16 A
Input current limits	16 A
Load Capacity	3840 VA

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Output

Maximum Total Current Draw per Phase	16 A
Number of power socket outlets	1 IEC 60309 16 A 2P+E
Cord Length	3 ft (0.91 m)

Conformance

Product Certifications	CE EMC Directive 2004/108/EC Low Voltage Directive 2006/95/EC
Standards	EN/IEC 60950-1 UL 60950-1

Environmental

Ambient air temperature for operation	23...113 °F (-5...45 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)

Ordering and shipping details

GTIN	731304333418
Package weight(Lbs)	13.12 lb(US) (5.95 kg)

Packing Units

Package 1 Height	4.49 in (11.4 cm)
Package 1 width	23.62 in (60 cm)
Package 1 Length	13.74 in (34.9 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------